

# Vacc-Safe

## Pharmacy Refrigerator

### VS135



#### LED Display

Microprocessor control, digital display and temperature adjustment with an increment of 0.1 °C.

#### Multiple Alarm Functions

Capable of alerting failures due to high and low temperature, sensor error, power failure, low battery, door ajar and remote alarm.

#### Ergonomic Design

810mm cabinet height makes it easy to place under test bench, saving storage space.

#### Lockable Design

Safety lock to prevent unauthorized access.

#### Superior Cabinet Temperature Uniformity, Auto Defrost

The test point of performance in the cabinet increased from 2 points to 9 points.

#### Energy Efficient Hydrocarbon (HC) Refrigeration System

Optimised refrigeration system, utilising high-efficiency HC compressor significantly reduces energy consumption.

#### Greener by Design

HC refrigerants are natural non-toxic and more environmentally friendly.

SPECIALISTS IN MEDICAL REFRIGERATION AND EQUIPMENT

# EURO CHILL

## Specifications



# VS135

### Technical Data

Cabinet Type	Upright, glass door
Climate Class	N
Cooling Type	Forced air cooling
Defrost Mode	Auto
Refrigerant	HC
Noise (dB (A))	41

### Performance

Temp Range (°C)	2~8
-----------------	-----



### Control

Controller	Microprocessor
Display	LED

### Electrical Data

Power Supply (V/Hz)	220-240/50 (60)	115/50 (60)
Power (W)	230	230
Electrical Current (A)	1.5	1.5

### Construction

Capacity (L/Cu.Ft)	118/4.2	
Net/Gross Weight (approx)	(kg)	46/51
	(lbs)	101.5/112.5
Interior Dimension (W*D*H)	(mm)	515*415*630
	(in)	20.3*16.3*24.8
Exterior Dimension (W*D*H)	(mm)	597*635*810
	(in)	23.5*25.0*31.9
Packing Dimension (W*D*H)	(mm)	680*690*910
	(in)	26.8*27.2*35.8

### Accessories

Caster	Y
Foot	Y
Porthole	Y
Shelves/Drawers	3/1

### Alarms

High/Low Temp	Y
Remote Alarm	Y
Power Failure	Y
Sensor Error	Y
Low Battery	Y
Door Ajar	Y

### Certification

CE	Y
UL	Y

SPECIALISTS IN MEDICAL REFRIGERATION AND EQUIPMENT  
**EURO CHILL**

F1 / 13-15 Kevlar Close  
 Braeside, Vic 3195  
 1300 459 140