VS1300PSS BIOMEDICAL REFRIGERATOR

Vacc-Safe

Vacc-Safe Medical refrigerators are suitable for storing vaccines, medicines and laboratory products between 2°C and 8°C in pharmacies, hospitals, medical clinics and laboratories.



Self Closing Door

Avoid letting the heat in by accident.



Lockable

Additional security for pharmaceuticals and samples.



Security

Audible and Visual Alarms. Safety Lock.



Single LED Display

High accuracy single LED displays.



LED Touch Screen Controller.

Our LED touch screen controller allows users to easily read, record and control the Refrigerator's current temperature, as well as recording the minimum and maximum.





Self Closing Doors.

This Refrigerator is equipped with self closing lockable doors to ensure that products are kept at a safe temperature and the doors cannot be left open when the unit is unattended. The unit is also equipped with a fan cut out switch that enables the fan to cut out once the door is open.

VS1300PSS BIOMEDICAL REFRIGERATOR Vacc-Safe

Item	Model No.	VS1300PSS
Product structure data	Temperature Range	2~ 8°C
	Fridge Storage Volume(L)	1300 L Nett
	Product Dimensions(mm)(wxdxh)	1314*845*2105
	Packing Dimensions(mm)(wxdxh)	1368*889*2147
	Net/Gross Weight	190/241
Technical data	Compressor type	Fixed frequency
	Cooling Type	Fan forced cooling
	Defrost type	Auto
	Climate Class	N
	Rated Voltage/Frequency(V/Hz)	220V/50Hz
	Rated Power(W)	390
	Rated Current(A)	2.8
	Decibel rating	N/A
	Refrigerant/Amount(g)	R134a/400g
Control	Temp HI/LOW reset	N
	Sensor Qty	2
	Sensor Type	NTC
	Controller	Microprocessor
	Display	LED display
Product Performance	Temperature Accuracy	+/-2°C
	Temperature uniformity/°C	+/-2°C
	Sound Alarm	Υ
Alarms	Light Alarm	Υ
	Power Failure Alarm	Υ
	Sensor Failure Alarm	Υ
	Environment Temperature Alarm	Υ
	Door ajar Alarm	Υ
	High Temperature Alarm	Υ
	Low Temperature Alarm	Υ
	Remote Alarm	N
Accessories	USB	N
	Anti-condensation Door	N
	Lock	Υ
	Backup Battery	N
	Backup Battery Endurance	N/A
	Shelves/Drawers Qty	12 Shelves
	Cable Port	N
	Castors/type	4 (2 omni directional)

