

VS528SF SPARK FREE REFRIGERATOR

Vacc-Safe

Vacc-Safe Spark Free Laboratory refrigerators are suitable for storing vaccines, medicines and laboratory products between 2°C and 10°C in pharmacies, hospitals, medical clinics and laboratories.



Self Closing Door

Avoid letting the heat in by accident.



Security

Audible and Visual Alarms.
Safety Lock.



Lockable

Additional security for pharmaceuticals and samples.



Single LED Display

High accuracy single LED displays.



Zoning Requirements.

All of our Vacc-Safe Spark Free refrigerators have a top mounted compressor in order to meet Hazardous areas zoning requirement 2, which requires a fridge or freezer compressor system to be 300mm above floor level.

LED Touch Screen Controller.

Our LED touch screen controller allows users to easily read and record the Refrigerators current temperature and also its highest and lowest.

CFC-Free Refrigerant.

This Provides controlled temperature conditions with all Vacc-Safe Spark Free models using a digital temperature controller with HI/LO temperature memory.



Item	Model No.	VS528SF
Product structure data	Temperature Range	2~ 10℃
	Fridge Storage Volume(L)	528L Nett
	Product Dimensions(mm)(wxdxh)	730*850*2190
	Interior Dimensions(mm)(wxdxh)	610*630*1360
	Packing Dimensions(mm)(wxdxh)	730*850*2190
	Net/Gross Weight	140/
Technical data	Compressor type	Fixed Frequency
	Cooling Type	Thermo Dynamic
	Defrost type	Auto
	Climate Class	N
	Rated Voltage/Frequency(V/Hz)	240V/50Hz
	Rated Power(W)	190
	Rated Current(A)	2.0
	Decibel rating	N/A
	Refrigerant/Amount(g)	R134a/R404a
Control	Temp HI/LOW reset	N
	Sensor Qty	2
	Sensor Type	NTC
	Controller	Digital
	Display	LED display
Product Performance	Temperature Accuracy	+/-0.1℃
	Temperature uniformity/℃	+/-2℃
	Sound Alarm	Y
Alarms	Light Alarm	Y
	Power Failure Alarm	Y
	Sensor Failure Alarm	Y
	Environment Temperature Alarm	Y
	Door ajar Alarm	Y
	High Temperature Alarm	Y
	Low Temperature Alarm	Y
	Remote Alarm	N
Accessories	USB	N
	Anti-condensation Door	N
	Lock	Y
	Backup Battery	N
	Backup Battery Endurance	N/A
	Shelves/Drawers Qty	4 Shelves
	Cable Port	N
	Castors/type	4 (2 omni directional)

