

Medi Guard Vaccine Refrigerators are suitable for storage of biological products, vaccines, drugs and reagents. Suitable for use in pharmacies, pharmaceutical factories, hospitals and medical clinics.



USB Data

Built in USB Data Logger.
Data can be traced and exported.



Single LED Display

High accuracy single
LED displays.



Temperature Control

High Precision
Temperature Control.



Security System.

Excellent alarm system that is equipped with a number of alarm functions including:



- High/low Temperature Alarm
- Door Ajar Alarm
- Power Failure Alarm
- Sensor Failure Alarm

Energy Saving and Environmentally Friendly.

This unit boasts a variable frequency compressor with an optimized cooling system which is proven to be energy saving. This type of compressor, along with the refrigerant are fluorine and chlorine free, making them better for the environment.

Microcomputer Temperature Control.

A high precision microcomputer temperature control system with built-in control and alarm sensors allows user to have the utmost control of their unit and ensure products are kept at the best temperature possible. The unit is also equipped with an easy to use LED controller.



Heated Door.

Equipped with a heated door, this refrigerator is perfect for product storage in warmer environments as there is no condensation on the outside of the unit.

| Item | Model No. | MG400PR |
|------------------------|--------------------------------|--------------------|
| Product structure data | Temperature Range | 2-8°C |
| | Fridge Storage Volume(L) | 400L |
| | Net/Gross Weight (kgs) | 116/139 |
| | Product Dimensions(mm)(wxdxh) | 665*710*1965 |
| | Interior Dimensions(mm)(wxdxh) | 530*555*1380 |
| | Packing Dimensions(mm)(wxdxh) | 690*790*2110 |
| Technical data | Cooling Type | Forced air cooling |
| | Defrost type | Auto |
| | Climate Class | N |
| | Rated Voltage/Frequency(V/Hz) | 220~240V/50Hz |
| | Rated Power(W) | 360 |
| | Rated Current(A) | 1.8 |
| | Decibel rating (dBA) | 43 |
| | Refrigerant/Amount(g) | R600a |
| | Sensor Qty | 2 |
| | Sensor Type | NTC |
| Control | Controller | Microprocessor |
| | High/low Temperature Reset | Y |
| | Display | LED display |
| Product Performance | Temperature Accuracy | +/-2 °C |
| | Temperature uniformity/°C | ±3°C |
| Alarms | Sound Alarm | Y |
| | Light Alarm | Y |
| | Power Failure Alarm | Y |
| | Sensor Failure Alarm | Y |
| | Low Battery Alarm | Y |
| | Door ajar Alarm | Y |
| | High Temperature Alarm | Y |
| | Low Temperature Alarm | Y |
| Remote Alarm | Y | |
| Accessories | USB | Y |
| | Door | Heated door |
| | Lock | Y |
| | Shelves/Drawers Qty | 7 shelves |
| | Cable Port | 1/25mm |
| | Castors/type | 4 |