

Vacc-Safe

Cosmetic Refrigerator

BT42 42 Litre

Suitable for storing **vaccines, medicines** and **laboratory products** between 2°C and 8°C in pharmacies, hospitals, medical clinics and laboratories.



Strong Cooling Airflow.

Downward airflow works as an air curtain to block the external hot air entering the refrigerator when a door is opened.



Increased Product Lifespan.

Dissipates heat 20% more effectively to improve life expectancy of core parts.




Heated Doors Stop Condensation Fog.

Accuracy within 0.1°C giving the utmost confidence that goods are stored with precision.



High Precision Temperature Control.

Accuracy within 0.1°C giving the utmost confidence that goods are stored with precision.



Improved Cooling Performance.

Patented Smart-Inverter technology significantly reduces the amount of energy consumed whilst maintaining superior temperature stability.



Built-In Backup Battery



Security



LED Display



DC Turbo Fan



Built-In Air Duct



Self Closing Door



USB Data

Vacc-Safe Australia's leading **vaccine** and **medical** cold storage **manufacturer**

1/13-15 Kevlar Cl Braeside, VIC 3195

(03) 8338 1205

query@vaccsafe.com.au

vaccsafe.com.au



Product structure data

| | |
|----------------------------------|-------------|
| Temperature Range | 2–6°C |
| Fridge Storage Volume (L) | 42L nett |
| Product Dimensions (mm) (wxdxh) | 480x465x575 |
| Interior Dimensions (mm) (wxdxh) | 400x360x425 |
| Packing Dimensions (mm) (wxdxh) | 520x530x640 |
| Net/Gross Weight | 23/26 |

Technical data

| | |
|--------------------------------|--------------------|
| Compressor Type | Fixed Frequency |
| Cooling Type | Forced air cooling |
| Defrost Type | No frost |
| Climate Class | N |
| Rated Voltage/Frequency (V/Hz) | 220V/50Hz |
| Rated Power (w) | 100 |
| Rated Current (A) | 0.75 |
| Decibel Rating (dBA) | 45 |
| Refrigerant/Amount (g) | R600/ 18g |

Control

| | |
|---------------------|----------------|
| Temp HI / LOW Reset | Y |
| Sensor Qty | 2 |
| Sensor Type | NTC |
| Controller | Microprocessor |
| Display | LED |

Product Performance

| | |
|---------------------------|-------|
| Temperature Accuracy | 0.1°C |
| Temperature uniformity/°C | ≤3°C |

Alarms

| | |
|-----|---|
| Yes | Sound, light, power failure, sensor failure, environment temperature, door ajar, high temperature, low temperature. |
|-----|---|

Accessories

| | |
|--------------------------|------------------|
| USB | Y |
| Anti-Condensation Door | Low-E Glass |
| Lock | Y |
| Backup Battery | Y |
| Backup Battery Endurance | 15h |
| Shelves/ Drawers Qty | 1 shelf/1 drawer |
| Cable Port | Y |
| Castors/type | N |