Vacc-Safe

Below Zero Freezer

VS-25L308 308 Litre

Suitable for storing **vaccines, medicines** and **laboratory products and samples** between -10°C and -25°C in pharmacies, hospitals, medical clinics and laboratories.





Microcomputer Temperature Control System.

Microcomputer temperature control – temperature accuracy 0.1°C Button-type control panel is easy to operate, the temperature and alarm settings can be adjusted on the panel..



Increased Product Lifespan.

Dissipates heat 20% more effectively to improve life expectancy of core parts.



Three-dimensional Seal.

The unique three-dimensional seal, through the double-layer door seal and the multi-layer airbag sealing design, can effectively reduce the leakage of cold air and achieve best thermal insulation performance.



High Precision Temperature Control.

Vacc-Safe® vaccine and medical cooling storage enables high precision temperature control and accuracy within 0.1°C giving the utmost confidence that goods are stored with precision. LBA Foaming Technology provides more effective insulation to improve performance and reduce overall energy consumption.



Built-In Backup Battery



Security



Single LED Display



USB Data



Lockable

Vacc-Safe

Below Zero Freezer VS-25L308 308 Litre



| Product structure data | |
|----------------------------------|--|
| Temperature Range | -10 to -25°C |
| Fridge Storage Volume (L) | 308L nett |
| Product Dimensions (mm) (wxdxh) | 700x690x1920 |
| Interior Dimensions (mm) (wxdxh) | 540x450x1277 |
| Packing Dimensions (mm) (wxdxh) | 755x715x2000 |
| Net/Gross Weight | 100/112 |
| | |
| Technical data | |
| Compressor Type | GMCC |
| Cooling Type | Direct Cooling |
| Defrost Type | Manual |
| Climate Class | N |
| Rated Voltage/Frequency (V/Hz) | 220V/50Hz |
| Rated Power (w) | 210 |
| Rated Current (A) | 1.18 |
| Decibel Rating (dBA) | 45 |
| Refrigerant/Amount (g) | R290 (110g) |
| | |
| Control | |
| Sensor Qty | 2 |
| Sensor Type | NTC |
| Controller | Microprocessor |
| Display | LCD |
| | |
| Product Performance | |
| Temperature Accuracy | 0.1°C |
| Temperature uniformity/°C | ≤3.5°C |
| | |
| Alarms | |
| | Power failure, sensor failure, environment |
| Yes | temperature, door ajar, high temperature, low temperature, remote. |
| | |
| Accessories | |
| USB | Υ |
| Door Heating | Υ |
| Lock | Υ |
| Backup Battery | Υ |
| Backup Battery Endurance | 20h |
| Shelves/Drawers Qty | 7 Drawers |
| Cable Port | Υ |
| Castors/type | 4 castors (front 2 lockable) |