# Vacc-Safe

#### **Vaccine Refrigerator**

VS150 150 Litre

Suitable for storing **vaccines, medicines** and **laboratory products** between 2°C and 8°C in pharmacies, hospitals, medical clinics and laboratories.





#### Strong Cooling Airflow.

Downward airflow works as an air curtain to block the external hot air entering the refrigerator when a door is opened.



#### Increased Product Lifespan.

Dissipates heat 20% more effectively to improve life expectancy of core parts.



## High Precision Temperature Control.

Accuracy within 0.1°C giving the utmost confidence that goods are stored with precision.



### Improved Cooling Performance.

Patented Smart-Inverter technology significantly reduces the amount of energy consumed whilst maintaining superior temperature stability.



Built-In Backup

**Battery** 



Security



LCD Display



DC Turbo Fan



**USB Data** 



**Built-In Air Duct** 



Self Closing Door





#### Vaccine Refrigerator VS150 150 Litre



Product structure data	
Temperature Range	2-8°C
Fridge Storage Volume (L)	150L nett
Product Dimensions (mm) (wxdxh)	595x615x810
Interior Dimensions (mm) (wxdxh)	505x467x620
Packing Dimensions (mm) (wxdxh)	665x675x860
Net/Gross Weight	42/48

Technical data	
Compressor Type	Fixed Frequency
Cooling Type	Forced air cooling
Defrost Type	No frost
Climate Class	N
Rated Voltage/Frequency (V/Hz)	220V/50Hz
Rated Power (w)	100
Rated Current (A)	1.0
Decibel Rating (dBA)	45
Energy Consumption kWh(24h)	0.78
Refrigerant/Amount (g)	R600
Control	
Temp HI / LOW Reset	N
Sensor Qty	3
Sensor Type	NTC
Controller	Microprocessor
Display	LCD

Product Performance	
Temperature Accuracy	0.1°C
Temperature uniformity/°C	≤2°C

Alarms	
	Sound, light, sensor failure, door ajar,
Yes	high temperature, low temperature.

Accessories	
USB	Υ
Anti-Condensation Door	Low E glass
Lock	Υ
Controller Backup Battery	Y/20h
RS485	Υ
Shelves/ Drawers Qty	2 Shelves
Cable Port	Υ
Castors/type	N
Warranty	24 months