# Vacc-Safe

### **Premium Refrigerator** VS50 50 Litre

Suitable for storing **vaccines**, **medicines** and **laboratory products** between 2°C and 8°C in pharmacies, hospitals, medical clinics and laboratories.





# $\sim$





#### Strong Cooling Airflow.

Downward airflow works as an air curtain to block the external hot air entering the refrigerator when a door is opened.

#### Increased Product Lifespan.

Dissipates heat 20% more effectively to improve life expectancy of core parts.

#### Heated Doors Stop Condensation Fog.

Accuracy within 0.1°C giving the utmost confidence that goods are stored with precision.

#### High Precision Temperature Control.

Accuracy within 0.1°C giving the utmost confidence that goods are stored with precision.

#### Improved Cooling Performance.

Patented Smart-Inverter technology significantly reduces the amount of energy consumed whilst maintaining superior temperature stability.



Vacc-Safe Australia's leading vaccine and medical cold storage manufacturer

## Vacc-Safe

## Premium Refrigerator VS50 50 Litre

| Product structure data           |             |
|----------------------------------|-------------|
| Temperature Range                | 2-8°C       |
| Fridge Storage Volume (L)        | 50L nett    |
| Product Dimensions (mm) (wxdxh)  | 480x465x575 |
| Interior Dimensions (mm) (wxdxh) | 400x360x425 |
| Packing Dimensions (mm) (wxdxh)  | 520x530x640 |
| Net/Gross Weight                 | 23/26       |

| Technical data                 |                    |
|--------------------------------|--------------------|
| Compressor Type                | Fixed Frequency    |
| Cooling Type                   | Forced air cooling |
| Defrost Type                   | No frost           |
| Climate Class                  | Ν                  |
| Rated Voltage/Frequency (V/Hz) | 220V/50Hz          |
| Rated Power (w)                | 100                |
| Rated Current (A)              | 0.75               |
| Decibel Rating (dBA)           | 45                 |
| Refrigerant/Amount (g)         | R600/ 18g          |
| Energy Consumption (kwh/24h)   | 0.65               |
| Control                        |                    |
| Temp HI / LOW Reset            | Υ                  |
| Sensor Qty                     | 2                  |
| Sensor Type                    | NTC                |
| Controller                     | Microprocessor     |
| Display                        | LED                |

| 0.1°C |
|-------|
| ≤3°C  |
|       |

| Alarms      |   |
|-------------|---|
| Yes         | Sound, light, power failure, sensor failure,<br>environment temperature, door ajar, high<br>temperature, low temperature. |
| Accessories |   |

| Accessories              |                  |
|--------------------------|------------------|
| USB                      | Υ                |
| Anti-Condensation Door   | Low-E Glass      |
| Lock                     | Υ                |
| Backup Battery           | Υ                |
| Backup Battery Endurance | 15h              |
| Shelves/ Drawers Qty     | 1 shelf/1 drawer |
| Cable Port               | Υ                |
| Castors/type             | Ν                |
| Warranty                 | 24 months        |

Vacc-Safe Australia's leading vaccine and medical cold storage manufacturer



