Vacc-Safe

Combined Fridge/Freezer

VSC-25L506

Vacc-Safe medical Refrigerators and Freezers can be used in hospitals, epidemic prevention stations, universities and scientific research institutes.





Top Cooling.

Strong cooling airflow from the top to the bottom, works as an air curtain to block the external hot air from entering the refrigerator when the door is opened.



Increased Product Lifespan.

Dissipates heat 20% more effectively to improve life expectancy of core



Multi-layer Silicone Sealing Structure.

Provides a tight seal between inner and outer door for better insulation.



Improved Cooling Performance.

Patented Smart-Inverter technology significantly reduces the amount of energy consumed whilst maintaining superior temperature stability.



Built-In Controller Backup Battery



Security



LED Display



USB Data



Lockable

Vacc-Safe

Combined Fridge/Freezer VSC-25L506 506L



1920 mm

| Product structure data | |
|----------------------------------|------------------------|
| Temperature Range | Fridge 2°C to 8°C |
| | Freezer -10°C to -25°C |
| Fridge Storage Volume (L) | Fridge 247L |
| | Freezer 259L |
| Product Dimensions (mm) (wxdxh) | 866x811x1920 |
| Interior Dimensions (mm) (wxdxh) | Fridge 680x596x630 |
| | Freezer 680x620x650 |
| Packing Dimensions (mm) (wxdxh) | 905x835x2025 |
| Net/Gross Weight | 141/163 |

| Technical data | |
|--------------------------------|---|
| Compressor Type | Fixed Frequency |
| Cooling Type | Fridge, Forced air cooling Freezer, Direct Cooling |
| Defrost Type | Fridge, Auto defrost |
| | Freezer, Manual defrost |
| Climate Class | N |
| Rated Voltage/Frequency (V/Hz) | 220V/50Hz |
| Rated Power (w) | 340 |
| Rated Current (A) | 3.0 |
| Energy Consumption (kwh/24h) | 1.4 |
| Decibel Rating (dBA) | 50 |
| Refrigerant/Amount (g) | mixed |

| Control | |
|-------------|----------------|
| Sensor Qty | 4 |
| Sensor Type | NTC |
| Controller | Microprocessor |
| Display | LED |

| Product Performance | |
|---------------------------------|--------|
| Controller Temperature Accuracy | 0.1°C |
| Temperature uniformity/°C | ≤1.5°C |

| Alarms | |
|--------|---|
| Yes | Sound, light, power failure, sensor failure, environment temperature, door ajar, high temperature, low temperature, remote. |

| Accessories | |
|---------------------------------|----------------------|
| USB | Υ |
| Lock | Υ |
| Backup Battery | Υ |
| Backup Battery Endurance | 15h |
| Shelves/ Drawers Qty | Fridge 3/ Freezer 3 |
| Cable Port | Υ |
| Castors/type | 2 + 2 Levelling Feet |
| | |

