

Vacc-Safe

Cosmetic Refrigerator

BT42 42 Litre

Suitable* for storing **vaccines, medicines** and **cosmetic products** between 2°C and 8°C in pharmacies, hospitals and medical/ beauty clinics.



Increased Product Lifespan.

Dissipates heat 20% more effectively to improve life expectancy of core parts.



Specific Temperature Range For Cosmetics.

This product can be used to store human testing samples, drugs, vaccines, biological products, reagents etc as well as items that need to be stored at the ambient temperature of 2-8°C.



High Precision Temperature Control.

Accuracy within 0.1°C giving the utmost confidence that goods are stored with precision.

* This unit is not suitable for use inside a cupboard or any other confined space.



Built-In Backup Battery



Security



LED Display



DC Turbo Fan



Built-In Air Duct



Self Closing Door



USB Data

Vacc-Safe Australia's leading **vaccine** and **medical** cold storage **manufacturer**

1/13-15 Kevlar Cl Braeside, VIC 3195

(03) 8338 1205

query@vaccsafe.com.au

vaccsafe.com.au



Product structure data

Temperature Range	2–8°C
Fridge Storage Volume (L)	50L gross
Product Dimensions (mm) (wxdxh)	450x459x570
Interior Dimensions (mm) (wxdxh)	380x300x410
Packing Dimensions (mm) (wxdxh)	520x530x640
Net/Gross Weight	23/26

Technical data

Compressor Type	Fixed Frequency
Cooling Type	Forced air cooling
Defrost Type	No frost
Climate Class	N
Rated Voltage/Frequency (V/Hz)	220V/50Hz
Rated Power (w)	100
Rated Current (A)	0.75
Decibel Rating (dBA)	45
Refrigerant/Amount (g)	R600

Control

Temp HI / LOW Reset	Y
Sensor Qty	2
Sensor Type	NTC
Controller	Microprocessor
Display	LED

Product Performance

Controller Temperature Accuracy	0.1°C
Temperature uniformity/°C	≤3°C

Alarms

Yes	Sound, light, power failure, sensor failure, environment temperature, door ajar, high temperature, low temperature.
-----	---

Accessories

USB	Y
Anti-Condensation Door	Low-E Glass
Lock	Y
Backup Battery	Y
Backup Battery Endurance	15h
Shelves/ Drawers Qty	1 shelf/1 drawer
Cable Port	Y
Castors/type	N