

Vacc-Safe



CO2 Backup System

CO2 backup systems are designed to ensure optimal safety for critical samples stored in Ultra Low Temperature Freezers. When the temperature in the freezer rises above a preset value, the backup system injects liquid CO2 into the freezer via an electromagnetic valve.

Key features and advantages

- Compact design with a small footprint, can easily be placed on top of ULT Freezers.
- Temperature display and adjustable set point
- Test button to check that the electromagnetic valve is functioning correctly.
- Multiple alarms
- Low-pressure CO2 alarm reminds users to replace CO2 cylinder promptly;
- Rechargeable battery with 48 hours working time
- Stops injecting CO2 when the door is opened to protect users
- Standard metal hoses (connecting reserve system and cylinder) and CO2 injection tube included, no additional preparation needed



Vacc-Safe

CO2 Backup System



Model VBS-C

Model VBS-C		
Basic Information	Climate Type	N/ST/T
	Cooling Method	Direct Cooling
	Refrigerant	Liquid CO2
Performance	Cooling Temperature (°C)	-70°C
	Temperature Range (°C)	-40 to -70°C
Control	Display	LED
	Temperature Increment	1°C
Power	Power Supply	AC 100-240V, 50/60Hz
	Power (W)	20
	Current(A)	0.25
Weight and size	Net/Gross Weight	10.2/13.6 KG
	External dimensions (W*D*H)	200*410*160
	Packing dimensions (W*D*H)	370*530*330
Function	High/Low Temperature Alarm	Y
	Low Battery Alarm	Y
	Sensor Fault Alarm	Y
	Main Power Outage Alarm	Y
	Electromagnetic Valve Open Indicator Light	Y
	Mains Power Supply Indicator Light	Y
	Electromagnetic Valve Test Button	Y
Accessories	Metal Hose	3 meters as standard
	Injection Pipe	2 meters as standard