

# Vacc-Safe

## Premium Solid Door Refrigerator


VS1006PSD 1006 Litre

Suitable for storing **vaccines, medicines** and **laboratory products** between 2°C and 8°C in pharmacies, hospitals, medical clinics and laboratories.



### Strong Cooling Airflow.

Downward airflow works as an air curtain to block the external hot air entering the refrigerator when a door is opened.




### Increased Product Lifespan.

Dissipates heat 20% more effectively to improve life expectancy of core parts.



### High Precision Temperature Control.

Accuracy within 0.1°C giving the utmost confidence that goods are stored with precision.



### Improved Cooling Performance.

Patented Smart-Inverter technology significantly reduces the amount of energy consumed whilst maintaining superior temperature stability.



Built-In Controller Backup Battery



Security



Dual LED Display



DC Turbo Fan



Built-In Air Duct



Self Closing Door



USB Data



**Vacc-Safe** Australia's leading **vaccine** and **medical** cold storage **manufacturer**

1/13-15 Kevlar Cl Braeside, VIC 3195

(03) 8338 1205

query@vaccsafe.com.au

[vaccsafe.com.au](http://vaccsafe.com.au)



### Product structure data

Temperature Range	2–8°C
Fridge Storage Volume (L)	1006L nett
Product Dimensions (mm) (wxdxh)	1220x808x1920
Interior Dimensions (mm) (wxdxh)	1130x634x1354
Packing Dimensions (mm) (wxdxh)	1280x835x2085
Net/Gross Weight	220/260

### Technical data

Compressor Type	Inverter
Cooling Type	Forced air cooling
Defrost Type	No frost
Climate Class	N
Rated Voltage/Frequency (V/Hz)	220V/50Hz
Rated Power (w)	350
Rated Current (A)	2.1
Decibel Rating (dBA)	60
Refrigerant/Amount (g)	R600
Energy Consumption (kwh/24h)	2.0

### Control

Temp HI / LOW Reset	Y
Sensor Qty	6
Sensor Type	NTC
Controller	Microprocessor
Display	LED (Temperature & Humidity)

### Product Performance

Temperature Accuracy	0.1°C
Temperature uniformity/°C	≤3°C

### Alarms

Yes	Sound, light, power failure, sensor failure, environment temperature, door ajar, high temperature, low temperature, remote.
-----	---

### Accessories

USB	Y
Anti-Condensation Door	Solid Door
Lock	Y
Backup Battery	Y
Backup Battery Endurance	24h
Shelves/ Drawers Qty	10 Shelves
Cable Port	Y
Castors/type	4 (Omni directional)
Warranty	24 Months

