

# Vacc-Safe

## Vaccine Refrigerator

VS1366P 1366 Litre

Suitable for storing **vaccines, medicines** and **laboratory products** between 2°C and 8°C in pharmacies, hospitals, medical clinics and laboratories.



### Inbuilt USB Data Logger.

Data can be traced and exported from the refrigerator itself to give the most accurate data readings.



### Top Cooling Technology


Strong cooling airflow from the top to the bottom, works as an air curtain to block the external hot air from entering the refrigerator when door is opening, so as to prevent the temperature in the cabinet from rising rapidly, also contributes better temperature uniformity



### High Precision

#### Temperature Control.

Accuracy within 0.1°C giving the utmost confidence that goods are stored with precision.



### Dual Guard Cooling.

Two independent Inverter Compressors work together to ensure optimal cooling inside the refrigerator. If one compressor fails, the other will keep the fridge running.



**Built-In Backup Battery**



**Security**



**LCD Display**



**DC Turbo Fan**



**USB Data**



**Built-In Air Duct**



**Self Closing Door**

**Vacc-Safe** Australia's leading **vaccine** and **medical** cold storage **manufacturer**

1/13-15 Kevlar Cl Braeside, VIC 3195

(03) 8338 1205

[query@vacccsafe.com.au](mailto:query@vacccsafe.com.au)

[vacccsafe.com.au](http://vacccsafe.com.au)

### Product structure data

Temperature Range	2-8°C
Fridge Storage Volume (L)	1366L nett
Product Dimensions (mm) (wxdxh)	1500x895x1925
Interior Dimensions (mm) (wxdxh)	1410x660x1540
Packing Dimensions (mm) (wxdxh)	1600x990x2200
Net/Gross Weight	227/271

### Technical data

Compressor Type	Inverter
Cooling Type	Forced air cooling
Defrost Type	Auto
Climate Class	N
Rated Voltage/Frequency (V/Hz)	220V/50Hz
Rated Power (w)	750
Rated Current (A)	5.0
Decibel Rating (dBA)	45
Energy Consumption kWh(24h)	7.0
Refrigerant/Amount (g)	R600a

### Control

Temp HI/ LOW Reset	N
Sensor Qty	10
Sensor Type	NTC
Controller	Microprocessor
Display	LCD

### Product Performance

Controller Temperature Accuracy	0.1°C
Temperature uniformity/°C	≤1°C

### Alarms

Yes	Sound, light, sensor failure, door ajar, high temperature, low temperature.
-----	---

### Accessories

USB	Y
Anti-Condensation Door	Low E glass with heating
Lock	Y
Controller Backup Battery	Y/40h
Shelves/ Drawers Qty	12 Shelves
Cable Port	Y
Castors/type	5/2 leveling feet
Warranty	24 months

