

# Vacc-Safe

## Premium Refrigerator VS390P 390 Litre

Suitable for storing **vaccines, medicines** and **laboratory products** between 2°C and 8°C in pharmacies, hospitals, medical clinics and laboratories.



### Strong Cooling Airflow.

Downward airflow works as an air curtain to block the external hot air entering the refrigerator when a door is opened.



### Stainless Steel Interior.

Corrosion resistant, durable and easy to clean 304 Stainless Steel coats the inside of the refrigerator. Stainless steel is also non-absorbent and highly hygienic.




### Heated Doors Stop Condensation Fog.

Accuracy within 0.1°C giving the utmost confidence that goods are stored with precision.



### Increased Product Lifespan.

Dissipates heat 20% more effectively to improve life expectancy of core parts.



### Improved Cooling Performance.

Patented Smart-Inverter technology significantly reduces the amount of energy consumed whilst maintaining superior temperature stability.



**Built-In Controller  
Backup Battery**



**Security**



**Dual LED  
Display**



**DC Turbo  
Fan**



**Built-In Air  
Duct**



**Self Closing  
Door**



**USB Data**



**Vacc-Safe** Australia's leading **vaccine** and **medical** cold storage **manufacturer**

1/13-15 Kevlar Cl Braeside, VIC 3195

(03) 8338 1205

[query@vaccsafe.com.au](mailto:query@vaccsafe.com.au)

[vaccsafe.com.au](http://vaccsafe.com.au)



### Product structure data

<b>Temperature Range</b>	2-8°C
<b>Fridge Storage Volume (L)</b>	416L nett
<b>Product Dimensions (mm) (wxdxh)</b>	690x653x1920
<b>Interior Dimensions (mm) (wxdxh)</b>	595x514x1343
<b>Packing Dimensions (mm) (wxdxh)</b>	755x715x2000
<b>Net/Gross Weight</b>	88/107

### Technical data

<b>Compressor Type</b>	Inverter
<b>Cooling Type</b>	Forced air cooling
<b>Defrost Type</b>	No frost
<b>Climate Class</b>	N
<b>Rated Voltage/Frequency (V/Hz)</b>	220V/50Hz
<b>Rated Power (w)</b>	260
<b>Rated Current (A)</b>	1.7
<b>Decibel Rating (dBA)</b>	55
<b>Refrigerant/Amount (g)</b>	R600a
<b>Energy Consumption (kwh/24h)</b>	2.0

### Control

<b>Temp HI/ LOW Reset</b>	Y
<b>Sensor Qty</b>	5
<b>Sensor Type</b>	NTC
<b>Controller</b>	Microprocessor
<b>Display</b>	LED (Temperature & Humidity)

### Product Performance

<b>Temperature Accuracy</b>	0.1°C
<b>Temperature uniformity/°C</b>	≤2°C

### Alarms

Yes	Sound, light, power failure, sensor failure, environment temperature, door ajar, high temperature, low temperature, remote.
-----	---

### Accessories

<b>USB</b>	Y
<b>Anti-Condensation Door</b>	Electrical heating
<b>Lock</b>	Y
<b>Controller Backup Battery</b>	Y
<b>Backup Battery Endurance</b>	15h
<b>Shelves/ Drawers Qty</b>	5 Shelves
<b>Cable Port</b>	Y
<b>Castors/type</b>	4 (Omni directional)
<b>Warranty</b>	24 Months

